



RING SIZES: This weave is possible with almost any ring size, within an Aspect Ratio range of 2.7 (tight) - 4.2 (lots of movement)

Suggested Sizes for Bracelet:

L16 base metal

L = 1/4" (6.4 mm)

16g SWG = 0.062" (1.6 mm)

J14 sterling silver

J = 7/32" (5.6 mm)

14g AWG = 0.064" (1.6 mm)

12 rings per inch

Suggested Sizes for Earrings:

H18 base metal

H = 3/16" (4.8 mm)

18g SWG = 0.04" (1.2 mm)

H17 sterling silver

H = 3/16" (4.8 mm)

17g AWG = 0.04" (1.15 mm)

16 rings per inch

Suggested Sizes for Necklace:

T14* base metal

T = 3/8" (9.5 mm)

14g SWG = 0.08" (2.0 mm)

8 rings per inch

X12* base metal

X = 7/16" (11.1 mm)

12g SWG = 0.10" (2.6 mm)


7 rings per inch

**These sizes take hand strength to manipulate. We also recommend using heavier pliers such as medium flat-nose Wubbers or Duck Bills.*


PREP: Pre-close 2/3 of the rings and open the rest.

1. Put 2 closed rings on an open, and close the open ring.
2. Scoop up another 2 closed on a new open ring, and weave the open through the ring you just closed in step 1. Close the open ring.

3. Separate the 2 hanging rings.



4. Once again, scoop up 2 closed rings on a new open rings and weave through the middle ring of the previous unit. Close the open ring. Continue weaving in this manner until reaching your desired length.



FINISHING: For earrings, you can attach the earwire directly to your strand of shaggy loops as shown in the image above. For a bracelet, we recommend using a couple F18 rings to taper down and attach your toggle. To see a diagram for how we like to finish the necklace, visit our website at:

B3supplies.com/go/shaggy